

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 July 2004 (15.07.2004)

PCT

(10) International Publication Number
WO 2004/059398 A2

- (51) International Patent Classification⁷: G04G 3/00
- (21) International Application Number: PCT/IB2003/005820
- (22) International Filing Date: 5 December 2003 (05.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
- | | | |
|------------|-------------------------------|----|
| 02080543.8 | 30 December 2002 (30.12.2002) | EP |
| 03100861.8 | 1 April 2003 (01.04.2003) | EP |
| 03101946.6 | 30 June 2003 (30.06.2003) | EP |
| 03102549.7 | 15 August 2003 (15.08.2003) | EP |
- (71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).


Siebe, T. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SCHELLMANN, Volker [DE/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DUINE, Peter, A. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LANGE, Ruediger, J. [DE/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). WILLEMSSEN, Oscar, H. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN WOUDEBERG, Roel [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). HOPPENBROUWERS, Jurgens, J., L. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). MARRA, Johannes [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: DEGUELLE, Wilhelmus, H., G.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,

[Continued on next page]

(54) Title: OPTICAL DISPLAY DRIVING METHOD



(57) Abstract: A display device comprising a plurality of pixels (26), a light source (23), and addressing means (24, 25) for coupling a selected pixel to said light source to thereby emit light, wherein the addressing means (24, 25) are arranged to address each pixel using pulse-width modulation (PWM). Further, the display comprises means (20) for amplitude modulating the intensity of said light source (23). The combination of the two modulations generates an exponentially distributed emitted light intensity, enabling proper gray scale rendering for a limited resolution in the time domain.